

# FWA-3140

## Rackmount Internet Security Platform with 4 Front LAN Ports/Dual PCI Expansion Slots/LCD Display

NEW



CE FCC

### Features

- 1U rackmount Internet security platform
- Socket 478 Intel® Pentium® 4
- Dual 32-bit/33 MHz PCI expansion slots
- Four 10/100 Fast Ethernet ports
- Console port for local setting
- Hard drive mounting bracket for 3.5" drive
- LCD display module

### Introduction

Conceived as a powerful rackmount Internet security platform, the FWA-3140 was specifically designed for Internet secure connectivity. Designed with the Intel® Pentium® 4 processor, it provides high performance and meets the requirements of Internet security appliances. The system supports CompactFlash for OS and Internet security applications. This avoids service disruption caused by hard disk mechanical/magnetic failures. In addition, the FWA-3140 can support system memory up to 2 GB DDR memory. Both CompactFlash and memory can be accessed and replaced for software upgrades through an easily removable cover. Designed with the Plug-and-Serve concept in mind, the FWA-3140 offers four 10/100 Mbps auto-sensing Fast Ethernet ports in the front panel. There are two LED Indicators which monitor power and HDD activities. For easy access, the front panel has a 9-pin, RS-232 serial port for local system management, maintenance and diagnostics. The FWA-3140 provides optional 3.5" IDE HDD and 2 PCI slots. It is FCC and CE compliant.

### Specifications

Processor System	CPU	Intel Pentium 4
	Max. Speed	533/400 MHz FSB
	L2 Cache	512/256KB
	Chipset	Intel 845GV ICH4
	BIOS	Award 2 Mb Flash
Memory	Technology	DDR 266/200
	Max. Capacity	2 GB
	Socket	184-pin DIMM x 2
Ethernet	Interface	10/100 Base-TX
	Controller	Intel 82551QM x 4
	Connector	RJ-45 x 4
Drive Bay	3.5" HDD	1
Cooling	Fan	1 (15 CFM)
	Blower	1
Management	Console	RS-232 x1
Miscellaneous	Control	Power supply
	Indicators	2 LED indicators for Power/HDD
	CompactFlash Socket	1
	LCD Display Module	1
Adapter Power Requirement	Input	AT PS, AC 90 ~ 264 V @ 47 ~ 63 Hz, full range
	Output	250 W
Environment	Temperature	Operating: 0 ~ 40 °C (32 ~ 104 °F) Non-Operating: -20 ~ 75 °C (-4 ~ 167 °F)
	Humidity	5 ~ 85 % @ 40 °C (104 °F) 5 ~ 95 %
	Physical	Dimensions (W x H x D): 426 x 44 x 350 mm (16.7" x 1.7" x 13.7") Weight: 4.5 Kg (9.9 lb)

