

# Smallest, Most Reliable Gigabit Switching Media Converter

Giga-MiniMc LFPT series



## PRODUCT FEATURES

- One 1000Base-SX or SFP fiber port
- One 10/100/1000 Mbps twisted pair port
- AutoCross automatic selection between crossover or straight-through connection
- Status LEDs
- LFPT permanently enabled
- 18 connections in the 1.5U high PowerTray/18 Chassis

Media conversion is the most cost-effective solution for extending the productive life of legacy wiring plants and equipment while allowing implementation of new technologies. Media conversion's greatest benefits are flexibility and cost savings.

Measuring less than 3.5 inches deep and 2 inches wide and having both data connections on the same side of the unit, the Giga-MiniMc-LFPT is the industry's smallest media converter and is a fraction of the cost of other alternatives.

Link Fault Pass Through (LFPT) is permanently enabled and a useful diagnostic feature that assists the network administrator in identifying a fault condition on a given segment between the interfaces. Plug-and-play operation with a variety of model types and powering options make the Giga-MiniMc LFPT easy and convenient to use.

## ORDERING INFORMATION

MODEL NUMBER	FIBER	FIBER PORTS	RANGE	ETHERNET PORTS	ETHERNET CONNECTOR
<b>Giga-MiniMc - with SFP/LFPT</b>					
856-11700	SFP	1	Various	1	RJ45
<b>Giga-MiniMc LFPT - Multi-Mode/Single-Mode</b>					
856-11701	SX-MM850-SC	1	220/500 m	1	RJ45
856-11702	MM1300-SC	1	5 km	1	RJ45
856-11703	SM1310-SC	1	10 km	1	RJ45
856-11704	SM1310/PLUS-SC	1	40 km	1	RJ45
<b>Giga-MiniMc LFPT - Single-Strand</b>					
856-11710	SSLX-SM1310-SC (1310xmt/1550rcv)	1	15 km	1	RJ45
856-11711	SSLX-SM1550-SC (1550xmt/1310-SC)	1	15 km	1	RJ45
856-11714	SSLX-SM1310/PLUS-SC (1310xmt/1550rcv)	1	40 km	1	RJ45

Note: SFP Fiber sold separately.

## ACCESSORIES - sold separately

806-39105 - DIN Rail Clip

806-39638 - Double-USB Power Cable, 0.9 m (36 in)

806-39650 - Barrel-Connector Power Cable, 0.3 m (12 in)

850-13086 - IE-PowerTray/18-AC (-20 to +70 °C), 18-slot AC Powered Chassis

895-39229 - Wall Mount Bracket

# Smallest, Most Reliable Gigabit Switching Media Converter

Giga-MiniMc LFPT series



## SPECIFICATIONS

TECHNICAL
Plug-and-play operation
RJ45 and SC or SFP connectors
IEEE 802.3 10Base-T twisted pair
IEEE 802.3u 100Base-TX twisted pair
IEEE 802.3ab 1000Base-T twisted pair
IEEE 802.3z 1000Base-LX or SX fiber
MTU: Supports Jumbo Frames up to 10240 bytes
Country-specific, high-reliability power adapter
Auto-Cross for MDI/MDIX
Layer 2 packet switching, store and forward (forwarding rate: 1,488,096 pps for 1000 Mbps)
Status LEDs

MECHANICAL	
Dimensions	2.11 x 4.57 x 8.51 cm (0.83h x 1.80w x 3.35"d)
Shipping Weight	.317 kg (0.7 lbs)
POWER	
	5 VDC, 600 mA
	120 VAC, 0.1A
ENVIRONMENTAL	
Operating Temperature:	0 to +50 °C (+32 to +122 °F)
Storage Temperature:	-35 to +75 °C (-31 to +167 °F)
Operating Humidity	5% to 95% (non-condensing)
REGULATORY APPROVALS	
	FCC Class A
	UL/cUL, CSA, CE

## MECHANICAL DIAGRAM

Units = in (mm)

