AIM-P508

Simple cradle for AIM 8" Industrial tablet



Features

- Compact and stylish cradle for AIM 8" industrial tablet
- Supports 5V/3A high speed charging to AIM 8" industrial tablet via Pogo Pin
- Supports multiple I/Os: 2 x USB 3.0 Type A; 1 x COM Ports; 1 x RJ45 ports
- Suitable for retail customer to do table-site ordering and information checking
- · Provide another charging method to retail customer

CEFCC ROHS

Specifications

Model Name		AIM-P508A0	AIM-P508B0
Pogo Pin		5V/3A Charger	9V/2A Charger
Thermal Printer		N/A	N/A
I/O Port		1 x DC IN (micro USB type with 5V/3A input) 1 x USB 2.0 Type A	1 x DC IN (DC Jack with 12V/3A input) 2 x USB 3.0 Type A 1 x COM Port (RS232) 1 x RJ45
Dimensions		138 x 167 x 98 mm	
Environment	Operating Temperature	0 ~ 40° C	
	Storage Temperature	-10 ~ +60° C	
	Operating Humidity	5% ~ 95%, non-condensing	

Ordering Information

P/N	Description
AIM-P508A0	Charging, 1 x USB 2.0 Type A; 1x DC in (micro USB)
AIM-P508B0	Charging, 2 x USB 3.0 TypeA; 1 x COM Ports; 1 x RJ45 ports, 1 x DC in Jack (12V only)

Packing List

Item	AIM-P508A0	AIM-P508B0
1	Simple cradle (USB & charging only) x 1	Simple cradle (Full I/O) x 1
2		Power adapter x 1

Fully-Integrated I/O





